



6' Wide Deluxe Enclosed Trailers

Specifications

GVWR	2,990 lb.
Max Payload	1,800 lb. if evenly distributed
External Length	10 ft. or 12 ft. plus 18 in. of usable space in the nose of the V.
External Width	6 ft.
Interior Height	6 ft. 6 in. at center
Interior Width	5 ft. 10 in.
Exterior Skin	.030 painted aluminum (color choices available for same price)
Rear Door Type	Barn doors or ramp gate - same price for either. Door opening is 5 ft. 2 in. wide and 6ft. tall.
Side Door Type	32 in. - RV style
Main Frame	3 in. x 2 in. tubing main frame and tongue
Floor Crossmembers	Formed channels - 16 in. o.c.
Wall Studs	1 in. x 1.25 in. tubing - 16 in. o.c.
Roof Members	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Type	One piece aluminum
Axles	3,500 lb. EZ lube - 4 in. drop
Lighting	LED tail lights - LED bullet running lights
Tongue Jack	Top wind
Stoneguard	24 in. Starbright ATP - nose covered
Tires/Wheels	205/75 R15 Radial Load range C - on silver mod steel wheels
Fenders	Brushed aluminum
Coupler	2 in. a-frame
Floor	3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet
Interior Liner	3/8 in. Dry Max
Roof Vent	Side vent air scoops are standard
Style of Front	V-nose
Exterior Fasteners	Screw down - 16 in. o.c.