



6' Wide Standard Enclosed Trailers

Specifications

GVWR	2,990 lb.
Max Payload	1,900 lb. if evenly distributed
External Length	10 ft. or 12 ft. plus 18 in. of usable space in the nose of the V.
External Width	6 ft.
Interior Height	6 ft. at center
Interior Width	5 ft. 10 in.
Exterior Skin	.024 painted aluminum (white only)
Rear Door Type	Barn doors or ramp gate - same price for either. Door opening is 5 ft. 2 in. wide and 5 ft. 6 in. tall.
Side Door Type	32 in. - plant made (on models with door)
Main Frame	3 in. x 2 in. tubing main frame and tongue
Floor Crossmembers	Formed channels - 24 in. o.c.
Wall Studs	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Members	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Type	Galvalume
Axles	3,500 lb. EZ lube - 4 in. drop
Lighting	LED tail lights - incandescent running lights
Tongue Jack	Top wind
Stoneguard	16 in. Starbright ATP
Tires/Wheels	205/75 D15 Bias Load range C - on silver mod steel wheels
Fenders	Brushed aluminum
Coupler	2 in. a-frame
Floor	3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet
Interior Liner	Luan
Roof Vent	N/A
Style of Front	V-nose
Exterior Fasteners	Screw down - 24 in. o.c.