



## 7' Wide Premium Enclosed Trailers

### Specifications

GVWR	7,000 lb.
Max Payload	5,300 lb. on 14 ft. - 5,000 on 16 ft. - 4,800 on 18 ft. - if evenly distributed
External Length	14 ft., 16 ft., or 18 ft. plus 18 in. of usable space in the nose of the V.
External Width	7 ft. plus fenders - 8 ft. 6 in. at outside of fenders
Interior Height	6 ft. 6 in. at center
Interior Width	6 ft. 9 in.
Exterior Skin	.030 painted aluminum (color choices available for same price)
Rear Door Type	Barn doors or ramp gate - same price for either. Door opening is 6 ft. 2 in. wide and 6 ft. tall.
Side Door Type	32 in. - RV style with flush lock and bar lock
Main Frame	4 in. x 2 in. tubing main frame and tongue
Floor Crossmembers	Formed channels - 16 in. o.c.
Wall Studs	1 in. x 1.25 in. tubing - 16 in. o.c.
Roof Members	1 in. x 1.25 in. tubing - 16 in. o.c.
Roof Type	One piece aluminum
Axles	3,500 lb. EZ lube - 4 in. drop RUBBER TORSION
Lighting	LED tail lights - LED slim line running lights
Tongue Jack	Zinc plated front wind jack with sand foot
Stoneguard	24 in. 045 ATP - V-nose covered
Tires/Wheels	205/75 R15 Premium Westlake Radial Load range D - on aluminum spoke wheels
Fenders	Brushed aluminum - tandem tear drop
Coupler	2 5/16 in. a-frame
Floor	3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet
Interior Liner	3/8 in. Dry Max - High Tech enclosed trailer wall material - does not swell when it gets wet
Roof Vent	Side vent air scoops are standard
Style of Front	V-nose
Exterior Fasteners	Bonded screwless exterior