



7' Wide Deluxe Enclosed Trailers

Specifications

| | |
|--------------------|--|
| GVWR | 7,000 lb. |
| Max Payload | 5,350 lb. on 14 ft. - 5,135 on 16 ft. - 4,900 on 18 ft. - if evenly distributed |
| External Length | 14 ft., 16 ft., or 18 ft. plus 18 in. of usable space in the nose of the V. |
| External Width | 7 ft. plus fenders - 8 ft. 6 in. at outside of fenders |
| Interior Height | 6 ft. 6 in. at center |
| Interior Width | 6 ft. 9 in. |
| Exterior Skin | .030 painted aluminum (color choices available for same price) |
| Rear Door Type | Barn doors or ramp gate - same price for either. Door opening is 6 ft. 2 in. wide and 6ft. tall. |
| Side Door Type | 32 in. - RV style - flush lock handle |
| Main Frame | 4 in. x 2 in. tubing main frame and tongue |
| Floor Crossmembers | Formed channels - 16 in. o.c. |
| Wall Studs | 1 in. x 1.25 in. tubing - 16 in. o.c. |
| Roof Members | 1 in. x 1.25 in. tubing - 24 in. o.c. |
| Roof Type | One piece aluminum |
| Axles | 3,500 lb. EZ lube - 4 in. drop. Brakes on all four wheels. |
| Lighting | LED tail lights - LED bullet running lights |
| Tongue Jack | Zinc plated front wind jack with sand foot |
| Stoneguard | 24 in. Starbright ATP - nose covered |
| Tires/Wheels | 205/75 R15 Radial Load range C - on silver mod steel wheels |
| Fenders | Brushed aluminum - tandem tear drop |
| Coupler | 2 5/16 in. a-frame |
| Floor | 3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet |
| Interior Liner | 3/8 in. Dry Max |
| Roof Vent | Side vent air scoops are standard |
| Style of Front | V-nose |
| Exterior Fasteners | Screw down - 16 in. o.c. |