



8.5' Wide Deluxe Enclosed Trailers

Specifications

GVWR	7,000 lb. or 9,990 lb.
Max Payload	For 7,000 lb. GVWR - 4,200 lb. on 20 ft. For 9,990 lb. GVWR - 7,000 lb. on 20 ft. - 6,500 on 24 ft. - 6,000 on 28 ft. All payload ratings are for an evenly distributed load.
External Length	20 ft., 24 ft., 28 ft.
External Width	8 ft. 5 in. at outside of fenders
Interior Height	6 ft. 6 in. at center
Interior Width	8 ft. (81 in. between wheel boxes)
Exterior Skin	.030 painted aluminum (color choices available for same price)
Rear Door Type	Barn doors or ramp gate - same price for either. Door opening is 7 ft. 5 in. wide and 6ft. tall.
Side Door Type	32 in. - RV style - flush lock handle
Main Frame	6 in. x 2 in. tubing main frame and tongue
Floor Crossmembers	Formed channels - 16 in. o.c.
Wall Studs	1 in. x 1.25 in. tubing - 16 in. o.c.
Roof Members	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Type	One piece aluminum
Axles	3,500 lb. or 5,200 lb. spring suspension EZ lube - 4 in. drop. Brakes on all four wheels.
Lighting	LED tail lights - LED bullet running lights
Tongue Jack	Zinc plated front wind jack with sand foot
Stoneguard	24 in. Starbright ATP - nose covered
Tires/Wheels	205/75 R15 Radial Load range C - on silver mod steel wheels for 3,500 lb. axles. 225/75 R15 Radial Load range D -on silver mod steel wheels for 5,200 lb. axles.
Fenders	Brushed aluminum
Coupler	2 5/16 in. a-frame
Floor	3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet
Interior Liner	3/8 in. plywood
Roof Vent	Side vent air scoops are standard
Style of Front	V-nose
Exterior Fasteners	Screw down - 16 in. o.c.