



8.5' Wide Standard Enclosed Trailers

Specifications

GVWR	6,000 lb.
Max Payload	3,540 lb. on 20 ft. - if evenly distributed
External Length	20 ft.
External Width	8 ft. 5 in. at outside of fenders
Interior Height	6 ft. at center
Interior Width	8 ft. (81 in. between wheel boxes)
Exterior Skin	.024 painted aluminum (white only)
Rear Door Type	Barn doors or ramp gate - same price for either. Door opening is 7 ft. 5 in. wide and 5 ft. 6 in. tall.
Side Door Type	32 in. - plant made (on models with door)
Main Frame	6 in. x 2 in. tubing main frame and tongue
Floor Crossmembers	Formed channels - 24 in. o.c.
Wall Studs	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Members	1 in. x 1.25 in. tubing - 24 in. o.c.
Roof Type	Galvalume
Axles	3,500 lb. EZ lube - 4 in. drop. Brakes on all four wheels.
Lighting	LED tail lights - incandescent running lights
Tongue Jack	Top wind
Stoneguard	16 in. Starbright ATP
Tires/Wheels	205/75 R15 Radial Load range C - on silver mod steel wheels
Fenders	Brushed aluminum - tandem tear drop
Coupler	2 5/16 in. a-frame
Floor	3/4 in. Dry Max - High Tech enclosed trailer floor material - does not swell when it gets wet
Interior Liner	Luan
Roof Vent	N/A
Style of Front	V-nose
Exterior Fasteners	Screw down - 24 in. o.c.